



# **Energy Calibration of the PANDA Electromagnetic Calorimeter**

#### Hang Qi

On behalf of IHEP/USTC group

September, 2021

### Outline

- PANDA EMC-Barrel
- Energy Calibration
- Energy Leakage Correction
- Calibration with Leakage Correction
- Summary

#### **PANDA EMC-Barrel**

- Energy measurement
- Position measurement
- Shower shape measurement
- Separation of  $\gamma/e$  and hadrons

#### **PWO-II crystal:**

- Width ~ 2-3 cm ( $R_M$  ~ 2 cm)
- Length ~ 20 cm ( $X_0$  ~ 1 cm)



## Energy Calibration $(\pi^0 \rightarrow \gamma \gamma)$

- Detection unit uniformity
- Pre-shower and Leakage
- Light yield non-uniformity

The calibration will improve the energy resolution and correct the reconstructed energy to the true energy which can be used in physics analysis.



## Energy Calibration ( $\pi^0 \rightarrow \gamma \gamma$ )

#### • Monte Carlo simulated sample of $\pi^0 o \gamma\gamma$



## Energy Calibration $(\pi^0 \rightarrow \gamma \gamma)$

- The calibration algorithm can be applied to those crystals in the inner region of the calorimeter, and perfectly satisfy the requirement of PANDA experiment
- However, the calibration algorithm will suffer the energy leakage problem when applied to crystals in the edge region
- The energy leakage problem must be solved before doing calibration





- Influences of energy leakage :
  - Shower lost → energy shift
  - Statistics lost → bad resolution
  - •
- Solutions:
  - MPV shift
  - Estimate the leakages based on some features of the shower lateral development, such as the shape of the shower...

#### Monte Carlo simulated sample of single y



• When a coming particle hit the edge of the EMC, the energy deposited in the outer side will not be detected.



The energy deposited in the outer side  $(E_{Outer})$  is missed for edge condition, but the ratio  $E_{Outer}/E_{Seed}$  can be obtained according to  $E_{Inner}/E_{Seed}$ 





Hang Qi (USTC)

**Calibration of the PANDA EMC** 





Hang Qi (USTC)

**Calibration of the PANDA EMC** 







Hang Qi (USTC)



Hang Qi (USTC)

**Calibration of the PANDA EMC** 



#### Hang Qi (USTC)



![](_page_18_Figure_1.jpeg)

![](_page_19_Figure_1.jpeg)

Hang Qi (USTC)

**Calibration of the PANDA EMC** 

![](_page_20_Figure_1.jpeg)

Hang Qi (USTC)

**Calibration of the PANDA EMC** 

![](_page_21_Figure_1.jpeg)

#### Hang Qi (USTC)

#### **Summary**

- A dedicated calibration algorithm is developed for the PANDA EMC, but it suffers the energy leakage problem;
- In order to improve the performance of the calibration algorithm, a solution for the energy leakage problem is presented.

![](_page_22_Figure_3.jpeg)

#### Thank you!

#### Backup

![](_page_25_Figure_0.jpeg)

![](_page_26_Picture_0.jpeg)

![](_page_26_Figure_1.jpeg)

#### Backup

![](_page_27_Figure_1.jpeg)

#### Backup

![](_page_28_Figure_1.jpeg)

![](_page_29_Figure_0.jpeg)

![](_page_29_Figure_1.jpeg)

![](_page_29_Figure_2.jpeg)

![](_page_29_Figure_3.jpeg)