

EMC Backward Endcap Status report


N. Baldicchi, L. Capozza , R. Gowdru , S. Katilmis , D. Liu, F. Maas,
J. Martínez, O. Noll , D. Rodríguez, C. Rosner, P. Schöner , S. Wolff

Panda Collaboration Meeting, EMC session
14. 6. 2023


Outline

- Submodule Production
- Submodule calibration status
- Status of electronics
- Update on DCS and SADC firmware status
- π^0 reconstruction from beamtime data
- Summary


PANDA Backward Endcap




Panda Version



Phase-0 Version



PANDA Backward Endcap



Submodule Production


- 640/640 crystals glued ✓
- 578/640 crystals wrapped

Submodule Production

- 640/640 crystals glued ✓
- 640/640 crystals wrapped ✓



Submodule Production

- 640/640 crystals glued ✓
- 640/640 crystals wrapped ✓
- 32/32 Full subunits built and pretested ✓






Submodule Production

- 640/640 crystals glued ✓
- 640/640 crystals wrapped ✓
- 32/32 Full subunits built and pretested ✓
- 1/16 Half subunits built






Submodule Production

- 640/640 crystals glued ✓
- 640/640 crystals wrapped ✓
- 32/32 Full subunits built and pretested ✓
- 14/16 half subunits built, pretests ongoing





Submodule Production

- 640/640 crystals glued ✓
- 640/640 crystals wrapped ✓
- 32/32 Full subunits built and pretested ✓
- 14/16 half subunits built, pretests ongoing
- Remaining 2 half subunits from prototype number 2





Submodule Calibration

- Fully automated calibration in climate chamber of:
 - Temperature sensors
 - Apd gain curve
 - Energy calibration with cosmics





Submodule Calibration

- Fully automated calibration in climate chamber of:
 - Temperature sensors
 - Apd gain curve
 - Energy calibration with cosmics
- Last meeting estimate:
72 hours for 3 submodules ➡ ~2 month for 48 submodules





Submodule Calibration

- Fully automated calibration in climate chamber of:
 - Temperature sensors
 - APD gain curve
 - Energy calibration with cosmics
- Last meeting estimate:
72 hours for 3 submodules ➡ ~2 month for 48 submodules
- Delay due to:
 - Noisy signals in climate chamber, Preventing energy calibration (solved)
 - SADCs were needed to develop Apfel and HV control with arduino (more later)
 - More details later by Samet





Lightpulsar system

- Lightpulsar system: individually adjustable lightpulsar for each crystal
- Design: one master PCB, 5 slave PCBS, 720 channels





Lightpulsar system

- Lightpulsar system: individually adjustable lightpulsar for each crystal
- Design: one master PCB, 5 slave PCBS, 720 channels
- Current status:
 - Mechanical parts all produced ✓





Lightpulsar system

- Lightpulsar system: individually adjustable lightpulsar for each crystal
- Design: one master PCB, 5 slave PCBS, 720 channels
- Current status:
 - Mechanical parts all produced ✓
 - 10/55 light fiber bundles are assembled and polished





Lightpulsar system

- Lightpulsar system: individually adjustable lightpulsar for each crystal
- Design: one master PCB, 5 slave PCBS, 720 channels
- Current status:
 - Mechanical parts all produced ✓
 - 55/55 light fiber bundles are assembled and polished ✓





Lightpulsar system

- Lightpulsar system: individually adjustable lightpulsar for each crystal
- Design: one master PCB, 5 slave PCBS, 720 channels
- Current status:
 - Mechanical parts all produced ✓
 - 55/55 light fiber bundles are assembled and polished ✓
 - Electronic components are there, PCBs ordered



Lightpulsar system

- Lightpulsar system: individually adjustable lightpulsar for each crystal
- Design: one master PCB, 5 slave PCBS, 720 channels
- Current status:
 - Mechanical parts all produced ✓
 - 55/55 light fiber bundles are assembled and polished ✓
 - PCBs are beeing assembled in house





HV distribution boards

- HV distribution boards:
 - Serial production of boards going on
 - 50 boards produced, 50 more to go





HV distribution boards

- HV distribution boards:
 - Serial production of boards going on
 - 50 boards produced, 50 more to go
- Calibration setup:
 - Calibration of HV DAC values
 - Calibration of HV ADC values





HV distribution boards

- HV distribution boards:
 - Serial production of boards going on
 - 50 boards produced, 50 more to go
- Calibration setup:
 - Calibration of HV DAC values
 - Calibration of HV ADC values
 - Calibration of current ADC values



HV distribution boards

- HV distribution boards:
 - Serial production of boards going on
 - 50 boards produced, 50 more to go
- Calibration setup:
 - Calibration of HV DAC values
 - Calibration of HV ADC values
 - Calibration of current ADC values
 - Mass calibration has started at room temperature



Apfel & HV control with Arduino

- Control of HV distribution boards and Apfel ASICs with arduino microcontroller instead of raspberry Pi
- Better scalability compared to Pi configuration

Apfel & HV control with Arduino

- Control of HV distribution boards and Apfel ASICs with arduino microcontroller instead of raspberry Pi
- Better scalability compared to Pi configuration
- Test setup established in laboratory, tests performed with submodule array in climate chamber
- System is running without major problems, should be ready to be deployed for the full detector



Epics integration

- Goal: Full integration of DCS into epics containers
- Status:
 - Fully integrated:
 - Control of high voltage crate
 - Control of low voltage crate
 - Light pulser

Epics integration

- Goal: Full integration of DCS into epics containers
- Status:
 - Fully integrated:
 - Control of high voltage crate
 - Control of low voltage crate
 - Light pulser
 - Control of Apfel preamplifier
 - Control of high voltage boards

Epics integration


- Goal: Full integration of DCS into epics containers
- Status:
 - Fully integrated:
 - Control of high voltage crate
 - Control of low voltage crate
 - Light pulser
 - Control of Apfel preamplifier
 - Control of high voltage boards
 - To be integrated:
 - Temperature sensors
 - Cooling with chiller

Epics integration

- Goal: Full integration of DCS into epics containers
- Status:
 - Fully integrated:
 - Control of high voltage crate
 - Control of low voltage crate
 - Light pulser
 - Control of Apfel preamplifier
 - Control of high voltage boards
 - To be integrated:
 - Temperature sensors
 - Cooling with chiller
- Additional DCS projects:
 - Temperature readout: app to show temperature gradient in submodules
 - Alert system for full detector



SADC firmware status

- Clock distribution via TRB3 SC is working





SADC firmware status

- Clock distribution via TRB3 SC is working
- Time Sorted Hit Packaging (Hits with the same raw time are collected in one package)
- Implementation on FPGA is done
- Receiver software is updated for the new data frame
- The first test with the prototype was successful




SADC firmware status

- Clock distribution via TRB3 SC is working
- Time Sorted Hit Packaging (Hits with the same raw time are collected in one package)
- Implementation on FPGA is done
- Receiver software is updated for the new data frame
- The first test with the prototype was successful
- First preparations for the chip2chip-bridge (Aurora) were done (aim: stream data from one FPGA to the other and use only one SFP to transfer data to the concentrator)




Electromagnetic shielding for FEE

- Design for electromagnetic shielding of frontend boards ongoing



Electromagnetic shielding for FEE



- Design for electromagnetic shielding of frontend boards ongoing
- Every modules need feedthroughs for:
 - Signal cables (linedriver boards)
 - Displayport cable (apfel&hv board control)



Electromagnetic shielding for FEE

- Design for electromagnetic shielding of frontend boards ongoing
- Every modules need feedthroughs for:
 - Signal cables (linedriver boards)
 - Displayport cable (apfel&hv board control)



⇒ modular design to have each submodules boards accessible



Electromagnetic shielding for FEE


- Design for electromagnetic shielding of frontend boards ongoing
- Every modules need feedthroughs for:
 - Signal cables (linedriver boards)
 - Displayport cable (apfel&hv board control)

⇒ modular design to have each submodules boards accessible
- Additional feedthroughs which serve multiple subunits:
 - Hv supply cables
 - Lv supply cables
 - Temperature sensors
 - Humidity sensors
 - Cooling pipes






Reconstruction of π^0

- Data from beamtime 2022
- Looking for coincident signal in both prototypes
- 2 SADC boards, different clocks
⇒ timestamps drift apart, synchronisation needed
- Lightpulsar events (every 5 sec.) for synchronisation



Reconstruction of π^0




- Data from beamtime 2022
- Looking for coincident signal in both prototypes
- 2 SADC boards, different clocks
 ➡ timestamps drift apart, synchronisation needed
- Lightpulsar events (every 5 sec.) for synchronisation



- ~1 h of data with Ta target
- Angles of prototypes: 14° and 18° , merged
- Coincidence time window: ± 300 ns, sideband region
- ~100 π^0 events with $\mu = 165.2 \pm 2.5$ MeV
 ➡ energy calibration needs to be improved
- Good energy resolution

Summary

- ▶ Submodule production:
 - Almost all submodules (full and half) are built and tested
 - Remaining 2 require disassembly of prototype
- ▶ Calibration of submodules:
 - Delay due to infrastructure needed for other projects
 - Projects finished → calibration can start
- ▶ Electronics:
 - HV boards: about half of series boards produced, calibration in progress
 - Lightpulsar system: fibrebundles all produced, PCB boards in production
 - Arduino Apfel&HV control: tested and working with climate chamber setup
- ▶ DCS:
 - Epics integration of Apfel-Asic control and HV board control finished



Thank You!