



MAX

MYRRHA ACCELERATOR eXPERIMENT
RESEARCH & DEVELOPMENT PROGRAMME



Accelerator Driven Transmutation

Jean-Luc BIARROTTE
CNRS-IN2P3 / IPN Orsay, France
EURATOM FP7 MAX project coordinator





MAX

MYRRHA ACCELERATOR eXPERIMENT
RESEARCH & DEVELOPMENT PROGRAMME




1. Introduction

- 2. The P&T strategy
- 3. The European ADS project: MYRRHA
- 4. ADS accelerator specificities
- 5. The MYRRHA accelerator R&D
- 6. Conclusion

High power proton accelerators

Production of **intense flux of secondary particles**
relevant for several domains of fundamental or applied science



✱ Muons, neutrinos...
for **Particle physics**



✱ **Neutrons** for condensed matter physics, material physics, irradiation, transmutation of long-lived nuclear wastes...

✱ Radioactive ions... for **Nuclear physics**

Example #1: SPIRAL-2 (GANIL) & EURISOL

✱ SPIRAL-2 project @ GANIL (Caen, F)

- Physics of exotic nuclei mainly, using the ISOL method
- Primary beams: protons, deuterons, heavy ions, up to 200 kW CW
- Phase 1 (driver linac) under construction



✱ EURISOL project

- New generation radioactive ion beam facility (ISOL method)
- Primary beams up to 5 MW

Example #2: SPL project (CERN)

★ SPL project @ CERN

- LHC luminosity upgrade
- Neutrino physics
(π , μ decay, or ${}^6\text{He}$, ${}^{18}\text{Ne}$ decay)
- Compatible with EURISOL
- LINAC 4 (160 MeV) under construction







Table 2: Low Power and High Power SPL beam characteristics

	LP-SPL	HP-SPL Option 1	HP-SPL Option 2
Maximum kinetic energy [GeV]	4	4 or 5 ^a	4 or 5 ^a
Average beam current during pulse [mA]	20	20	40 ^b
Pulsing rate [Hz]	2	50	50
Pulse duration [ms]	0.9	0.9	1.2 ^b
Beam power [MW]	0.14	2.25 @ 2.5 GeV or 4.5 MW at 5 GeV	5 @ 2.5 GeV and 4 MW at 5 GeV



^a Required for a neutrino factory.

^b Required for 2 simultaneous users of high beam power or for 5 MW at 2.5 GeV

Example #3: SNS (Oak Ridge, USA)




History of Beam Power on Target



SNS-03671-2005

Other machines & projects


✱ J-PARC facility (Japan)



✱ PSI (Switz.)




✱ ESS project (Sweden)



✱ MYRRHA project (Belgium)

✱ FAIR project (Germany)



✱ IFMIF project ✱ Project-X (USA)

Main associated challenges

These high power machines require an **excellent beam transmission** to be allowed to operate: beam loss level must be $< 10^{-6}$ per meter typically

✱ Physics of intense hadron beams

- Management of space charge effects
- Understanding of beam halo generation during transport

✱ R&D on new technologies

- Accelerating cavities (RFQ, superconducting cavities)
- Diagnostics for intense hadron beams
- New generation targets (MegaWatt)
- High power Radio-Frequency elements

✱ Increased demand for flexibility and reliability

- Higher & higher beam availability is required
- High diversity of primary beam in a single machine (nuclear physics application)
- Beam interruptions forbidden (ADS application)



MAX

MYRRHA ACCELERATOR EXPERIMENT
RESEARCH & DEVELOPMENT PROGRAMME



1. Introduction

2. The P&T strategy

3. The European ADS project: MYRRHA

4. ADS accelerator specificities

5. The MYRRHA accelerator R&D


6. Conclusion

Nuclear wastes

- About 2500 tons of Spent Nuclear Fuel are produced every year by the 145 reactors of EU
- High Level Wastes represent 0.2% in volume & 95% in radiotoxicity and are long-term dominated by **Minor Actinides** (MA, especially ^{241}Am)
- Reference solution for HLW management = long-term **geological disposals**




*The Yucca Mountain Nuclear Waste Repository (USA)
project de-funded in 2011*



Motivation for Partitioning & Transmutation

- **Partitioning & Transmutation (P&T) strategy:** reduce radiotoxicity, volume and heat loads of long-lived nuclear wastes (MA) before geological storage




H. Aït Abderrahim (SCK•CEN)

Present options for MA transmutation

Transmutation of MA into fission products is efficient only if:

- Fission to capture cross section ratio is high enough
- Enough neutrons are available to feed the transmutation process

=> **Need for a fast neutron spectrum**




In which type of fast reactor could we transmute ?

- In the next generation **GEN-IV nuclear power plants** (critical Fast Reactors)
 - ✓ homogeneous mode with low AM content in fuel (< 3%) for safety reasons
 - ✓ heterogeneous mode (MA blankets)
 - In a few **dedicated MA burners** (subcritical Accelerator Driven Systems), highly loaded with MA
- => sensitive compromise btwn **safety / economics / proliferation / politics...**

ADS (Accelerator Driven System)

ADS sub-critical systems = present reference solution for dedicated “transmuter” facilities

- Suited for various strategies on nuclear energy
- One “small” 400 MW_{th} industrial ADS could burn about 100kg of MA / year (→ 10 to 20 units for EU)



G. Van den Eynde (SCK•CEN)

ADS reactor specificities

- Neutron multiplication factor $k_{\text{eff}} < 1$ (typically between 0.93 & 0.97)
- Driven by external neutron source (proton beam + spallation target)
- No control rods, no safety rods
- Some very fast neutrons (> 20 MeV) in the core

$$P_{fi} = \eta_{sp} \cdot \frac{\varphi^* \cdot k}{\nu(1-k)} \cdot \frac{i}{C} \cdot E_f$$

where, η_{sp} = spallation neutron yield (≈ 30 for Pb target)
 k = neutron multiplication factor
 φ^* = source importance (≈ 1.5)
 ν = neutrons emitted per fission (≈ 2.5)
 E_f = energy generated per fission ($\approx 3.1 \times 10^{-10}$ W)
 i = accelerator current
 C = charge of a proton ($= 1.6 \times 10^{-19}$ C)

Background in France & Europe since 1990


- (FR) **Law « Bataille » n° 91-1381, 30 december 1991**
=> French roadmap for research on radioactive waste management
- (EU) ETWG report on ADS, 2001
- (EU-FP5) **PDS-XADS** project (2001-2004)
- (EU-FP6) **EUROTRANS** programme (2005-2010)
- (EU-FP7) On-going programmes (2011-2015)
- (FR) **Law n°2006-739, 28 june 2006**
=> Following-up the law « Bataille », with focus on sustainability




Article 3 (...) 1. La séparation et la transmutation des éléments radioactifs à vie longue. **Les études et recherches correspondantes sont conduites en relation avec celles menées sur les nouvelles générations de réacteurs nucléaires** mentionnés à l'article 5 de la loi n° 2005-781 du 13 juillet 2005 de programme fixant les orientations de la politique énergétique ainsi que sur les réacteurs pilotés par accélérateur dédiés à la transmutation des déchets, **afin de disposer, en 2012, d'une évaluation** des perspectives industrielles de ces filières et de mettre en exploitation un **prototype d'installation avant le 31 décembre 2020** ; (...)

A complex issue in even more complex hazards...

Energy demand growth



Changes in temperature, sea level and Northern Hemisphere snow





MAX

MYRRHA ACCELERATOR eXPERIMENT
RESEARCH & DEVELOPMENT PROGRAMME



1. Introduction

2. The P&T strategy

3. The European ADS project: MYRRHA

4. ADS accelerator specificities

5. The MYRRHA accelerator R&D

6. Conclusion

The MYRRHA project

MYRRHA Project

**Multi-purpose hYbrid Research Reactor for High-tech Applications
At Mol (Belgium)**

*Development, construction & commissioning of
a new large fast neutron research infrastructure
to be operational in 2023*

- ❶ **ADS demonstrator**
- ❷ **Fast neutron irradiation facility**
- ❸ **Pilot plant for LFR technology**


MYRRHA as an ADS demonstrator

Demonstrate the physics and technology of an Accelerator Driven System (ADS) for transmuting long-lived radioactive waste

- Demonstrate the **ADS concept** (coupling accelerator + spallation source + power reactor)
- Demonstrate the **transmutation** (experimental assemblies)

Main features of the ADS demo



50-100 MWth power
Highly-enriched MOX fuel
Pb-Bi Eutectic coolant & target
 k_{eff} around 0.95 in subcritical mode
600 MeV, 2.5 - 4 mA proton beam



MYRRHA reactor present layout



- Vessel
- Cover
- “Core barrel”
- Core support plate
- Core plug
- Above core structure
- Heat exchangers
- Pumps
- Diaphragm
- Core
- Fuel manipulators



MYRRHA as a fast spectrum irradiation facility

- All **European irradiation research reactors** are about to close within 20 years
- The **RJH** (Réacteur Jules Horowitz) project, is presently the only planned MTR (Material Tests Reactor), and provides mainly a thermal spectrum
- MYRRHA is the **natural fast spectrum complementary facility**

Réacteurs de recherche européens

<i>Pays</i>	<i>Réacteurs de recherche</i>	<i>Age en 2015 (ans)</i>
<i>Belgique</i>	<i>BR2 à Mol</i>	<i>52</i>
<i>Hollande</i>	<i>HRF à Petten</i>	<i>54</i>
<i>Norvège</i>	<i>HRP à Halden</i>	<i>55</i>
<i>France</i>	<i>Osiris à Saclay</i>	<i>49</i>
<i>Suède</i>	<i>R2 à Studsvik</i>	<i>Mis à l'arrêt en 2005</i>
<i>République tchèque</i>	<i>LVR15 à Řež</i>	<i>58</i>

Main applications of the MYRRHA irradiation facility

Test & qualification of innovative fuels and materials for the future Gen. IV fast reactor concepts (and for fusion energy)


Production of radio-isotopes for nuclear medicine (⁹⁹Mo especially)

Production of neutron irradiated silicon to enable technologies for renewable energies (windmills, solar panels, electric cars)

Fundamental science in general (also using the proton linac by itself)

MYRRHA as a Gen.IV demonstration reactor

Serve as a technology Pilot Plant for **liquid-metal based reactor concepts**
(LFR “Lead Fast Reactors”)



MYRRHA in brief

MYRRHA is considered as **a strategic stone**


- For **SCK•CEN**, as a replacement for the BR2 reactor (shut-down in 2026)
- For the European picture of **Material Testing Reactors**, as a complement to the RJH
- For the future of **sustainable nuclear energy**, as an ADS demonstrator & a strong support to the development of Gen. IV reactors



MYRRHA official key dates

- **1998:** first studies
- **2002:** pre-design “**Myrrha Draft 1**” (*cyclotron 350 MeV*)
- **2002-2004:** studied as one of the 3 reactor designs within the **PDS-XADS FP5 project** (*cyclotron turns into linac, fault-tolerance concept is introduced*)
- **2005:** updated design “**Myrrha Draft 2**” (*350 MeV linac*)
- **2005-2010:** studied as the XT-ADS demo within the **IP-EUROTRANS FP6 project** (*600 MeV linac conceptual design, R&D activities w/ focus on reliability*)
- **2010:** MYRRHA is on **the ESFRI list**, and is **officially supported by the Belgium government** at a 40% level (384M€, w/ 60M€ already engaged)
- **2010-2015:** engineering design, licensing process, set-up of the international consortium, w/ support from the **CDT, FREYA & MAX FP7 projects**
- **2016-2019:** construction phase
- **2020-2023:** commissioning and progressive start-up
- **2024:** full exploitation

MYRRHA within EURATOM FP7: 2010-2014





MAX

MYRRHA ACCELERATOR eXPERIMENT
RESEARCH & DEVELOPMENT PROGRAMME







1. Introduction
2. The P&T strategy
3. The European ADS project: MYRRHA

4. ADS accelerator specificities

5. The MYRRHA accelerator R&D
6. Conclusion

ADS proton beam requirements



ADS proton beam requirements


Proton beam general initial specifications within EUROTRANS

	Transmuter demonstrator (XT-ADS / MYRRHA project)	Industrial transmuter (EFIT)
Proton beam current	2.5 mA (& up to 4 mA for burn-up compensation)	~ 20 mA
Proton energy	600 MeV	800 MeV
Allowed beam trips nb (>3s)	~ <10 per 3-month operation cycle	~ < 3 per year
Beam entry into the reactor	Vertically from above	
Beam stability on target	Energy: $\pm 1\%$ - Current: $\pm 2\%$ - Position & size: $\pm 10\%$	
Beam time structure	CW (w/ low frequency 200 μ s beam “holes” for sub-criticality monitoring)	

Extreme reliability level

Multi MW class CW beams

The reliability requirement




Generic scheme of the European ADS accelerator

☀ Redundant injector

- Fault-tolerance is non applicable ($\beta < 0.15$)
- Minimized number of elements
- Spare stand-by injector with fast switching capabilities

☀ Modular SC main linac


- Upgradeable concept (demo, transmuter)
- Independently-controlled elements
- The function of a missing element can be replaced by retuning adjacent elements (“FAULT-TOLERANCE”)



Strategy for a fault case in the injector


① Initial configuration

Operational injector 1: RF + PS + beam ON



Warm stand-by injector 2: RF+ PS ON, beam OFF (on FC)

③ The failure is localized in injector




The switching magnet polarity is changed (~1s)

Need for an efficient fault diagnostic system !


② A failure is detected anywhere

Beam is stopped in injector 1 by the Machine Protection System @ t_0



④ Beam is resumed


Failed injector 1, to be repaired on-line if possible



Injector 2 operational (@ $t_1 < t_0 + 3\text{sec}$)

Strategy for a fault case in the main linac

- ✱ Based on the **local compensation** concept
 - If a SRF cavity system fails & nothing is done → beam is lost ($\beta < 1$)
 - If adjacent cavities operation points are properly retuned → nominal beam is recovered



- ✱ Such a scheme has been demonstrated at the SNS, and requires in MYRRHA:
 - **Independently-powered** RF cavities
 - **Operation margins** on accelerating fields and RF power amplifiers (typically +30%)
 - Tolerant beam dynamics design, with especially large **acceptance**
 - **Fast fault-recovery procedures** to perform the retuning within 3 seconds

Fast fault-recovery procedure




Figure 12 : Transverse beam distribution at 220 μ s, in red are plotted the losses

- ❶ A failure is detected anywhere
→ Beam is stopped by the MPS in injector at t_0
- ❷ The fault is localized in a SC cavity RF loop
→ Need for an efficient fault diagnostic system

❸ New field & phase set-points are updated in cavities adjacent to the failed one



→ Set-points previously determined at the commissioning & possibly stored in the LLRF systems FPGAs

❹ The failed cavity is detuned (to avoid the beam loading effect)

→ Using the Cold Tuning System

❺ Once steady state is reached, beam is resumed at $t_1 < t_0 + 3\text{sec}$

→ Failed RF cavity system to be repaired on-line if possible





MAX

MYRRHA ACCELERATOR eXPERIMENT
RESEARCH & DEVELOPMENT PROGRAMME




1. Introduction
2. The P&T strategy
3. The European ADS project: MYRRHA
4. ADS accelerator specificities

5. The MYRRHA accelerator R&D


6. Conclusion

Layout of the MYRRHA linac


INJECTOR BUILDING




Section #1 (Spoke $\beta \sim 0.35$ @ 352 MHz)




Layout of the MYRRHA linac




The 17 MeV MYRRHA injector



- ECR proton source (5 mA, 30 kV) + magnetic LEBT (L=2m)
- **4-rod RFQ 176 MHz** 1.5 MeV (Kilp = 1.0, V = 40kV, P < 25kW/m, L=4m)
- 176 MHz booster composed with **6 CH cavities** (2 Cu + 4 SC, L=7m)
- Unconventional but **very efficient solution** (low nb of elements, energy gain >1 MeV/m)
- **“Double-branch” MEBT** to connect the 2 injectors to the linac, including especially 2 achromatic deviations w/ a common switching magnet and 4 SC bunchers for long. matching




Beam dynamics in LEBT + RFQ



Related R&D → Source & RFQ



➤ R&D on the **MYRRHA 4-rod RFQ**

- ✓ Inspired from the SARAF experience
- ✓ **Enhanced reliability** by:
 - decreased voltages and power levels
 - improved silver-plated tuning plates
 - optimized cooling schemes for stems and rods
- ✓ Construction of a **short test section** to be tested at nominal power in 2012/2013



➤ **MYRRHA full injector test stand** in construction at UCL

- ✓ Source in 2013, RFQ in 2014





Related R&D → 176 MHz CH booster

➤ R&D on **room-temperature CH cavities**


- ✓ Detailed design of the 2 MYRRHA cavities
- ✓ Construction of a **short test section** to be tested at nominal power in 2013

➤ R&D on **superconducting CH cavities**

- ✓ Detailed design of the 4 MYRRHA cavities
- ✓ Construction of a **new prototype cavity** to be RF tested in 2012/13, and with beam at GSI in 2014/2015




The 600 MeV MYRRHA main linac




- **Spoke** 352 MHz SC cavities × 48 (1 family)
 - **Elliptical** 704 MHz SC cavities × 94 (2 families)
 - Modularity, conservative operation points & high acceptance to **ensure fault-tolerance**
- L=233 metres



Section #	#1	#2	#3
E_{input} (MeV)	17.0	80.8	183.9
E_{output} (MeV)	80.9	183.9	600.0
Cav. technology	Spoke	Elliptical	
Cav. freq. (MHz)	352.2	704.4	
Cavity geom. β	0.35	0.47	0.65
Nb of cells / cav.	2	5	5
Focusing type	NC quadrupole doublets		
Nb cav / cryom.	2	2	4
Total nb of cav.	48	34	60
Nominal E_{acc} (MV/m)	6.2	8.2	11.0
Synch. phase (deg)	-40 to -19	-38 to -15	
Beam load / cav (kW)	1.5 to 7.5	2.5 to 17	14 to 32
Section length (m)	68.6	63.9	100.8






Beam dynamics in MEBT + MAIN LINAC + HEBT





Related R&D → 352 MHz spoke cavities

- **Prototyping** of spoke cavities and ancillaries
- **Detailed design** for MYRRHA:
 - ✓ Cavity (prototype test in 2013)
 - ✓ Cryomodule (prototype test in 2015/2016)




Related R&D → 704 MHz elliptical SC cavities

- **Construction** of a $\beta=0.5$ prototype cryomodule
- **Commissioning** at low RF power in 2011/2012, and at 80 kW early 2013
- Is being used as a **test bench for reliability-oriented experiments** (fault-recovery procedures, smart regulation systems, reliability enhancement...)



SUPRA*Tech*
Institut de Physique Nucléaire Orsay



The MYRRHA final beam line



- Triple achromatic deviation w/ telescopic properties
- Beam scanning on the target window
- Highly remote-handled
- 2.4MW beam dump concept
- Spec. for beam diagnostics (inspired from PSI/SNS)
- First analysis of safety issues

Other R&D activities

- Development of a full **reliability model**
 - ✓ Preliminary results show that the goal of MTBF=250h should be reachable
 - ✓ 3 years of commissioning is foreseen at least to learn & improve machine operation
- **Beam dynamics** simulations
 - ✓ Benchmarking (e.g. TraceWin/Lorasz)
 - ✓ Optimisation of beam behaviour in main linac under nominal & fault operation
 - ✓ Start-to-end & Monte-Carlo error studies
- Design of the **2K cryogenic system**
- 700MHz **solid-state** amp. development
- Spec. for Instrumentation & Control
- Buildings design, cost analysis...





MAX

MYRRHA ACCELERATOR eXPERIMENT
RESEARCH & DEVELOPMENT PROGRAMME



1. Introduction
2. The P&T strategy
3. The European ADS project: MYRRHA
4. ADS accelerator specificities
5. The MYRRHA accelerator R&D

6. Conclusion

Summary

- **Nuclear waste management** is a complex (& long-term) issue in a much more complex (& shorter-term) hazard: sustainable energy & global warming
- **MYRRHA** = unique opportunity to demonstrate the ADS technology in a high-power scale
- At the end of the EURATOM FP7 projects (CDT, FREYA, **MAX**), the goal is to reach a sufficient level of design to be able to launch a construction phase for MYRRHA in 2015
- The **ADS accelerator reference scheme** is based on a 600 MeV, 4 mA cw superconducting proton LINAC
- R&D is focused on the **reliability issue**. This may bring substantial impact for availability optimisation in future accelerator projects featuring high power proton beams.



MAX

MYRRHA ACCELERATOR eXPERIMENT
RESEARCH & DEVELOPMENT PROGRAMME



Thank you for your attention !

COORDINATOR

<http://ipnweb.in2p3.fr/MAX/>

<http://myrrha.sckcen.be/>

