46th CBM Collaboration Meeting

Institute of Physics, Lanzhou, Gansu, China 2025-10-22 12:15 - 12:35





Dr. Eoin J. Clerkin

tel: (GSI ext) 2028

email: e.clerkin@gsi.de


KBW 4.006
Facility for Anti-proton and Ion Research in Europe
Planckstraße 1

Geometry and Parameter Community Management Tools






GitLab is an extension of git version control, which allows for collaborative development of software framework.





Redmine keeps track of known work-to-be-done as well as shared record of topic specific communication.



GitLab - HowTo Geometry or Parameter Submissions



- Spend 1 hour onboarding to Gitlab to save 10 hours by doing interactive howto prepared by Pierre-Alain https://git.cbm.gsi.de/notes/computing/gitlab-tutorial
- Below is the basic steps for making a submission to the geometry or parameter repo (or indeed cbmroot)

Steps to submit to the CBMROOT geometry repository.

- [1] Login/register for access to our git lab repository http://git.cbm.gsi.de
- [2] Make your own private fork of the cbmroot geometry repository
- https://git.cbm.gsi.de/CbmSoft/cbmroot_geometry
- [3] Clone your fork locally, i.e. `git clone git@git.cbm.gsi.de:your-username/cbmroot_geometry.git`
- [4] Make your changes and commit locally, i.e. 'git add subsystem.geo.root; git commit'
- [5] Git push remote to your own fork, i.e. 'git push'
- [6] Login in to the git lab. It will inform you that it has detected a recent push by you to the server.
- [7] Follow the large plus button and click "New merge request". Fill out the form requesting a merge between branch/fork of your change and the master branch of the "CbmSoft/cbmroot geometry"
- [8] Wait for someone on our side to accept the request, probably Florian or Pierre.

This follows the same steps for making a change to CbmRoot code base. If anything here is confusion a technical note and tutorial is available at

https://git.cbm.gsi.de/notes/computing/gitlab-tutorial/-/jobs/10802/artifacts/file/CBM_GitLab_Tutorial.pdf

Today's Agenda



Three main parts to this presentation:

- Overview of changes to geometry and parameter repositories
 - Focusing just on some highlights since last collaboration meeting
 - Pending merge requests
- Focus on the target region
 - Segmented and more exotic target types
 - Target Shells and update to the beam window
 - Target chamber
- Promotion of Geant4 over Geant 3
 - Requested V&V studies by detector groups

Pending Merge Request Geometry and Parameter GitLab Repos



Seometry Repo

Merged 249 Closed 74 All 326 Bulk edit New merge request 5 v Search or filter results... Priority ~ 1= Add TRD v25a geometry (Day1 Reduced Layer Spacing) As □ 6 of 8 !324 · created 1 month ago by Axel Puntke updated 4 days ago CodeOwners New MuCh geometry v23b As Re 12 of 14 12 1 1312 · created 3 months ago by Pawan Kumar Sharma updated 5 days ago CodeOwners Add MUST / PASTA to silver setup 5 of 5 checklist items completed □ □ 0 of 1 !294 : created 7 months ago by David Emschermann updated 3 months ago CodeOwners mCBM


arameter Repo




Realistic TRD frame My Request answered mostly











The additional complexity in the GDML files comes with GEANT simulation processing time increase (upper limit: +110% for TRD).

 Committed in trd_support branch https://git.cbm.gsi.de/trd/cbmsoft/cbmroot_geomet ry

Tessellated Objects


 Discussed for sometime and implemented twice, now the TRD has a realistic frame and available as default for simulation.





New RICH geometry My Request mostly answered







- Redesign of the mirror holders
- Replace old MirrorSupportBelts by new MirrorFixing which looks like the CAD model and the prototype
- Add a small plate at end of mirror support studs to fit the weight
- Fixing all overlaps in the geometry
- Fixing newly discovered bug in implementation of exit window
- change of geometry hierarchy at exit window
- similar change at entrance window to avoid potential of similar bug
- Additionally small changes (small regarding physics impact)
- changes in the volume hierarchy to reduce the depth
- changes in code of creator file to make it more efficient
- replacing some hard coded numbers by variables
- replacing double definitions of same volumes by copying




New MUCH geometry My Request is being answered










New MVD geometry My request resolved






- MVD issues at the 45th Collaboration
 - MVD hits not properly recreated. (resolved issue #3509)
 - MVD geometry sensor extent (resolved issue #3510)
- Main Issues resolved sitting down with Joachim on the Friday night of the 45th CBM CM.
- Ajit Kumar now takes over MVD software related tasks.







Motivation Why it must happen now?




- Requests for support for segmented targets and exotic target types.
- Target chamber tender, material study.
- Target exchanger with target shells
- BMON support code present in cbmroot for 1 year now.
- Lots of legacy work and geometries sitting in repo not actively being utilised by our analysis teams.
- This should all be implemented well in advance of the next VT in 2026

Segmented targets Support for standalone and exotic targets



- Coordinated and recorded in redmine #3695
- Merge request in draft mode Gitlab-2184 (not ready yet)

 Possible ring-shaped segmented targets in series from Tetayana's 2020 presentations. (see ref in #3695). Technical considerations nfor the target shell must also be considered.



 Clearly, support for a proton target will also be required, although I know of no discussions on this.

```
<position name="Layer 1" unit="mm" x="0.0"</pre>
v="0.0" z="1.0" />
<tube lunit="cm" name="layer" rmax="1.25"
deltaphi="360" z="0.025" />
<volume name="target" >
<materialref ref="vacuum" />
<solidref ref="world" />
<positionref ref="center" />
<physvol>
<volumeref ref="vol Be"/>
<positionref ref="center" />
</physvol>
<physvol>
<volumeref ref="vol Au"/>
<positionref ref="Layer 1" />
</physvol>
<physvol>
<volumeref ref="vol Pb"/>
<positionref ref="Layer-1" />
</physvol>
</volume>
```







target_v21b.geo.root

Present Focus on Target Region



Presentation given on Monday







- P.Dahm discussed the multiple affected system: BMON/T0, MVD, and STS. Similar to the CAD, multiple detector systems have to change in tandem.
- On the target shell of the target exchanger is current envisaged to be implemented for simulations.

Inclusion of the holding shell requires demotion of legacy target/MVD chamber





Volume in legacy target/MVD chamber is not large enough for a shell.




Shells available for some time, two issues prevent easy use for simulations.

target shell v21b.gdml

- Draft merge request for Target introduced as FairModule - #2184
 - Initial data has not correct placement.

basic upsteam pipe with updated beam window + STS beampipe





STS-Beam Pipe, ICM succeeded

ICM-Composites

- second prototype delivered
 - → verv satisfactory
- tested straight and within tolerances
- tested mechanically stable under vacuum
- tested vacuum tight
- mm wall thickness on tube
- 0.5 mm thickness on track membrane
- ~ 4 a/cm tube length



We will order a second one as spare

45th CBM collaboration meeting, GSI, Feb. 16 - 21, 2025

Candidate SIS100 beampipe geometries for simulation


Eoin Clerkin * Facility for Anti-Proton and Ion Research, Darmstadt, German

Several new beampipe simulation geometries were cre-ated during the course of last two years, though they were not widely distributed, in order not to confuse the commu-

titled whilst robustness of the technical design is assured, stated with robustness of the technical design is assured, as the control of the Reference [1] of this report, indirectly discusses the cre

contains the beampipe simulation geometry for the entire downstream section. Primarily, it comprises of downstream





cylinder, and the narrowed conic-based tube which trans-erses the REI/DMC/ILE devices these two sections, as bellow assembly (see Ref.[5]) is added to allow a deflec-tion angle for the beam between the downstream cylinder and narrowed conteal section. Creation of a ophisticated and transersed conteal section. Creation of a ophisticated in Ref. [4]. The bellow assembly is repossible for a sig-nificant percentage of the overall material badget of the beampipe as part of its structure and supports needs, and it was a noteworthy advanted to add a small deflection angle on the contraction of the structure and the structure of the object of the structure of the structure of the structure of the object of the structure of the structure of the structure of the object of the structure of the structure of the structure of the object of the structure o of 1.2" between the S15 and RR_UMULTH comic sections, so latter comic could have its directrix significantly reduced, reducing its material budget but more importantly the ma-terial budget of the entire bellows part. Ref. [6] highlights this case. It is a necessity for simulation geometries, un-like their CAD equivalents, to have an accurately specified


Inclusion

- Torodial window
- Initial cylindical section removed.
- Carbon fibre in tubular section reduced to 6 mm.





pipe_v22b beampipe with new beam window and target box






- CAD (see P.Dahm presentation) and GEANT used same schematic report for design so excellent agreement.
- Material study (steel, aluminium, carbon fibre) needed for tender proposal. See redmine https://redmine.cbm.gsi.de/issues/3719
- Mehul did the initial gdml implementation for the STS v22.





Embedded with -> full setup ->


 pipe_v22b is a version which combines these components together and the user may specify any angle for beam deflection. Some internal volumes in the bellows have been removed though.




BMON geometries




 CBM support provided and reported at the 43rd CBMCM



 Requires enlargement of the vaccumm structure before the target.








Planned steps for target region update



- Standalone volume for target. Placement of generated events has to be generalised. If done well, later steps may be simpler.
- New beampipe with beam window, sts beampipe, with integrated target chamber. Repositioned MVD detector may be needed.
- Target with integrated shell → Segmented targets → Complex annular targets.
- (Optionally) Inclusion of BMON, and integration of beam transport meters before the target. You may remember that the code base was included to facilitate a BMON detector for the 43rd Collaboration Meeting. (needs enlargement of the vaccuum space before target chamber)






Geant4 migration replacing Geant3 as the default transport engine



 You may recall Anna Senger and Florian Uhlig presentations at the 45th CBM Collaboration Meeting.





And of course, redmine will be used to managing and document this effort.

In Summary



- Motivated community encouraging software tools GitLab and Redmine through the not-so-suttle repetition throughout presention.
- Discussed the fulfilling of my geometry related requests by the RICH team, the TRD team, and the MUCH team since the last collaboration meeting fulfilling my redmine requests.
- Furture focus for big changes to the whole target region for the VT in 2026 and the next collaboration meeting.
- Highlight my many redmine requests for V&V studies for Geant4 migration over next months.
- And if you want to make me happy, change "new" to "in progress", "in-progress" to "resolved", and "resolved" to "closed" in your redmine issue.

