


Status of FTOF detectors

Petersburg Nuclear Physics
Institute (PNPI)

S.Belostotski

PANDA collaboration meeting March 2014





Motivations for FTOF


- PID of forward emitted particles with timing resolution of 50ps
- Work in coincidence with Barrel TOF
- Event start reference time with timing resolution of 50ps
- A high efficiency to detect anti hyperons, a good strangeness or charm (offline) trigger
- Can be used for determination of the drift time in DCs



FTOF wall

positioned at 7.5 m
from the IP

Central part
20 counters
20 plastic scintillators
Bicron 408
140x5x2.5 cm
40 Hamamatsu R4998 (1")




Side parts

2x23 counters
46 plastic scintillators
Bicron 408
140x10x2.5 cm
92 Hamamatsu R2083 (2")

light guides

Plexiglas, Mylar
wrapping



Bicron 408

(recommended for large TOF counters)

Rise time	0.9 ns
Decay time	2.1 ns
1/e light attenuation length	210cm
Wavelength of max emission	425nm


Fast PMTs (hamamatsu)

R4998 1" (R9800), R2083 2" (R9779)

Anode pulse rise time	0.7-1.8ns
TTS	250-370ps (FWHM)
Gain	1.1-5.7x10 ⁶
W.m. emission	420nm
HV	1500-3500v




Dipole TOF positioned inside the dipole magnet gap as planned for TDR



Projected 2x10 scintillation slabs 80÷100x10x2.5cm
readout from each end with Electron PMT 187

Diameter	30mm
Photocathode	20mm
Anode pulse rise time	1.4ns
TTS	$\approx 500\text{ps}$
Gain	5×10^5
W.m. emission	380nm (80% at 420nm)
HV	1800v



Caveat: have been tested in magnetic field less 0.5T

Alternative solution SiPMs provided timing resolution better than 100ps

Caveat: radiation hardness??

Not sensitive to mag. F.(!)

<i>SiPMs(hamamatsu)</i>	
<i>S10931-50p, S10931-100p</i>	
active area	3x3mm
Pixels	3600
Gain	$7.5 \times 10^5 - 2.4 \times 10^6$
W.m. emission	440nm
TTS	0.5-0.6ns(FWHM)



Selected aspects of Monte Carlo Studies




Time-of-flight PID with tracking and momentum analysis

$$m = p \sqrt{\frac{t^2}{t_c^2} - 1}$$

$$\frac{\delta m}{m} = \sqrt{\left(\frac{\delta p}{p}\right)^2 + \gamma^4 \left(\frac{\sigma_{TOF}}{t}\right)^2}$$

$t_c = L_{\text{track}} / c$ $L_{\text{track}} \simeq 7.5\text{m}$ (TOF wall position) $\sigma(\text{TOF}) = 50\text{--}100\text{ps}$




Comment: a good event start of 50ps provides if:
independent start counter available (no momentum info needed)
or RICH info or kinematical criteria



FTOF wall slab count rates

\bar{p} beam momentum, GeV/c	Pion rate, 1/s	Kaon rate, 1/s	Proton rate, 1/s	Antiproton rate, 1/s
2	3.9×10^5	2×10^3	1.2×10^4	1.07×10^6
5	6×10^5	7.8×10^3	3.8×10^4	9.5×10^5
15	9.6×10^5	4.7×10^4	3.2×10^4	8.2×10^5

@ HESR cycle averaged
Luminosity $10^{32} \text{ cm}^2\text{s}^{-1}$



@ 15 GeV/c pbar beam
normalized to $10^7/\text{s}$ interactions

all charged particles

total pbar rate

pbar from elastic scattering

charged particles produced in vacuum pipe







*e⁺e⁻ pairs produced by gammas from
pi⁰ decay in the target*



FTOF wall and barrel TOF multiplicities

0.14×10^6 \bar{pp} interactions generated

No dedicated start counter !




FTOF wall and barrel TOF interplay


FTOF/BTOF coincidence probabilities

2.5 GeV 23.6%


BTOF & FTOF coincidence




5. GeV 35.1%



10. GeV 45.4%



12.5GeV 48.3%



MC Simulation of $\bar{\Lambda}, \Lambda$ event selection

Under study are $\bar{p} + p \rightarrow \bar{\Lambda} + X$, $\bar{\Lambda} \rightarrow \bar{p} + \pi^+$
and $\bar{p} + p \rightarrow \Lambda + X$, $\Lambda \rightarrow p + \pi^-$

- DPM generator, PANDA root framework

$0.72 \times 10^6 \bar{p}p$ interactions @10 GeV

- Generated are $\pi^-, \pi^+, K^-, K^+, \bar{p}, p, \bar{\Lambda}, \Lambda$
- Produced particles are tracked through the solenoid and dipole magnetic fields and detected with FTOF wall scintillation counters

with

Particle momentum smearing
of

$$\frac{\sigma p}{p} = 0.01$$

Time-of-flight smearing of

$$\sigma TOF = 50 ps$$



Track length smearing
of

$$\sigma L = 1 cm$$

Production/decay vertex
separation



Generated Lambda hyperons



11



Detection Efficiency of FTOF wall

acceptance of FS $\pm 10\text{deg. hor.}$ $\pm 5\text{deg. ver.}$ $\rightarrow \Omega_{FS} = 0.09\text{sr}$

	Generated by DPM	Detected by FTOF wall	detection efficiency
π^-	880346	172188	0.195
π^+	877255	150440	0.171
K^-	30179	5820	0.192
K^+	26811	2863	0.107
p	453293	202174	0.446
\bar{p}	398323	51241	0.129
$\bar{\Lambda} \rightarrow \bar{p} + \pi^+$	19874	3840	0.193
$\Lambda \rightarrow p + \pi^-$	19518	≈ 100	$\approx 5 \cdot 10^{-3}$





Lambda Hyperon Event Selection



Event selection criteria

$$m(h^-) = m_p \quad m(h^+) = m_\pi \quad \text{and} \quad \Delta t_{\text{start}}^{\bar{p}\pi^+} > 100\text{ps}$$

$$m(h^+) = m_p \quad m(h^-) = m_\pi \quad \text{and} \quad \Delta t_{\text{start}}^{p\pi^-} > 100\text{ps} \quad \text{and} \quad z_2 > 6\text{mm}$$



$\bar{\Lambda}$ detected with high efficiency (20%) at weak selection criteria

$N_\Lambda / N_{\bar{\Lambda}} \approx 1/40$ Λ events also well detected



Experimental Study


of Timing Resolution

and


Prototyping




SiPM timing resolution



Variant A




Variant B



SiPM timing resolution is about 150ps

Test station for SiPM



Amplitude correction

$$\Delta t = \Delta t_0 - a \left(\frac{1}{\sqrt{q_1}} - \frac{1}{\sqrt{q_2}} \right) - b$$

Results variant B

Run	σ_0	σ_1	σ_2
40366	326	168	149
40367	497	170	142
40368	486	176	147

Results variant A

Run	σ_0	σ_1	σ_2
40366	608	195	157
40367	543	199	151
40368	557	193	150



PMT timing resolution using proton beams

PNPI 1 GeV synchrocyclotron

April 2009.

Optimization of slab thickness to 2.5 cm

Nov. 2012


Time resolution better 100ps

June 2013

Time resolution better 80 ps

Dec. 2013


Final results on prototyping




PMTs: R4998, R2083, Electron 187

COSY test beam in Juelich

Dec. 2012 test with TRB readout.
First “Electron” PMT187 test



Timing resolution measurements at 1 GeV PNPI SC



$S_3 S_4$ scintillation slabs B408:


length 100, 140cm

width 2.5, 5,10cm

thickness 1.5, 2.5cm

$S_1 S_2$ 1x1x1cm

R4998, R2083, Electron187



Hit position and pulse amplitude correction equation

calculated are τ_{13} , τ_{14} , τ_{34}

$$\tau_{nk} = t_n - t_k - a \left(\frac{1}{\sqrt{q_n}} - \frac{1}{\sqrt{q_k}} \right) - bx - c,$$

x hit position along the scintillation slab,

$\sigma(x) \approx 0.5$ mm defined by MWPCs

t_n, t_k measured with TDC, q_n, q_k measured with QDC,

a,b,c fitting parameters,

$\delta\tau_{nk}$ timing resolution (sigma of τ -distribution).


Proton energy $E_p = 730$ and
900MeV, $\sigma(E_p)$ about 0.5%

B408 thickness 2.5cm
Energy deposition 5MeV

Scintillation Efficiency
 10^4 photons/MeV



Timing resolution with R4998 and R2083




Summary of tests using proton beam

Scintillation slab dimensions	Photo multiplier tube	Comments
140 cm × 10 cm × 2.5 cm	Hamamatsu R 2083	75ps Accepted as a prototype for the FTOF wall
140 cm × 5 cm × 2.5 cm	Hamamatsu R 4998	70ps Accepted as a prototype for the FTOF wall
140 cm × 2.5 cm × 2.5 cm	Hamamatsu R 4998	60ps Variant of a prototype with smaller slab width
140 cm × 10 cm × 1.5 cm	Hamamatsu R2083	150ps Projected originally for the FTOF wall
140 cm × 5 cm × 1.5 cm	Hamamatsu R4998	120ps Projected originally for the FTOF wall
140 cm × 2.5 cm × 2.5 cm	Electron PMT 187	80ps Magnetic field protected, tentatively projected for the dipole TOF
100 cm × 10 cm × 2.5 cm	Electron PMT 187	150ps Magnetic field protected, tentatively projected for the dipole TOF


Time resolution R4998 and Electron187 with small scintillator (2x2x2cm) is 50 and 70ps, respectively.



FTOF wall mechanics.



FTOF wall front view



Scintillation counter mechanical components



Cost estimation update

FTOF wall

Plastic scintillators B408 20u.140x5x2.5cm+46u.140x10x2.5cm 60 k€

PMTs R9800 1" 600€ 40u. +5u.(spare) 27

PMTs, R9779 2" 900€ 92u.+10u.(spare) 92

Caveat: PMT R9800, , R9779 not on beam tested

FEE electronics 30

HV power supply 22

Gain monitoring system 9

Supporting structure (design, fabrication) 40

Test stand for mass production 35

Transportation, custom expenses 25

.....
340 k€

Dipole TOF

15

63

5

9

5

35 ??

132 k€

Infrastructure

- PNPI test beam
- PNPI design department (mechanical components drawings)
- PNPI electronic department (expertise, HV)
- PNPI Workshop (fabrication of mechanical components)
- Test station/preassembly in Juelich

From RRB February 2014 471 k€



PNPI group in PANDA



S.Belostotski	Stanislav	Prof.	Group leader
Gavrilov	Gennadij	Scient.	hardware
Izotov	Anton	Scient	R&D ,hardware, data analysis
Manaenkov	Sergej	Scient	theory, analysis
Miklukho	Oleg	Sen. Scient	R&D instrumentation
Naryshkin	Yuri	Scient	MC, data analysis
Suvorov	Kirill	PhD stud	MC, hardware
Veretennikov	Denis	PhD stud	MC, hardware, data analysis
Zhdanov	Andrey	Scient	R&D, hardware

Work Package 2014

Monte Carlo simulation In PANDAROOT Framework

- Study various PID options using TOF/DTOF/BTOF/ChTOF detectors;
- Optimize configuration of FTOF and DTOF in the dipole using benchmark reactions;
- Update rate calculations of Individual FTOF/DTOF slabs at max luminosity;

Design and prototyping

- Finalize prototyping FTOF counters with TRB;
- Complete study of PM-187 in strong magnetic field for DTOF prototyping, investigate SiPM variant
- Work out project of GMS
- Work out project of supporting mechanical structures and cabling

TDR approval September



Supporting slides



24

Global plan for FTOF / DTOF design, fabrication and installation 2014-2018

1. TDR approval, funding, tender,
agreement, manufacturing concept. from 01.01.2014 to 31.05.2015 17 months

2. Material procurement, manufacturing and
final prototype tests,
manufacturing all components,
detector pre-assembly. from 01.06.2015 to 31.03.2017 22 months

3. Shipment to FAIR: good inspection , test
inspection, approval for installation,
shipment from 01.04.2017 to 31.12.2017 9 months

4. Installation at HESR from 01.01.2018 to 30.09.2018 9 months

5. Commissioning from 01.10.2018 to 31.12.2018 3 months

M3 9/2014

M8 04/2016

M10 06/2017

M11 10/2018

Approval of TDR

Prototype tested
pre-series accepted

Approval for
installation

Ready for beam



SiPM Radiation Hardness Test @ 1GeV PNPI Proton Beam.


- The absolute beam intensity was determined in a standard way by measuring induced radioactivity of irradiated aluminum foils.
- The beam intensity during the tests was varied in the range $1.3 - 2.1 \times 10^8 \text{ cm}^{-2}\text{s}^{-1}$.
- The SiPM sample was not powered!
- Radiation was exposed in 10 successive periods about 10 minutes each. The integrated number of protons passing through the sensitive surface of the SiPM sample with the cross-section of $3 \times 3 \text{ mm}^2$ was 0.9×10^{11} . SiPM parameters (dark noise, amplitude and time characteristics for different values of high voltage) were measured before and after the radiation test using test station with ${}^{90}\text{Sr}$ electron source.

U,V	I, μA	A, mV	Noise	Noise+ ${}^{90}\text{Sr}$
72.06	0.15	40	1550	8700
72.53	0.30	80	4230	18500
72.06	81.0	4	2800	6200
72.53	113.0	6	99000	102000



As it is seen from the table the SiPM was practically killed by this dose the value of which can be taken as upper limit,

- Yet it is important to find out at which dose the sample start malfunctioning,
- It is also important to compare irradiation effect on unpowered and powered samples,
- All this will constitute our experimental program with SiPM samples.

$\Delta T = 0.056 \text{ } ^\circ\text{C}$ *this is not heat!*




SiPM's @ OLYMPUS. DESY TB22.




Counters: 8mm/2SiPM's, 4mm/2SiPM's (corners), 4mm/2SiPM's (sides),
Readout: 25x preamp (electronics workshop, KPH Mainz)

- QDC spectra to see light yield,
- QDC spectra with prescaled baseline trigger mixed into determine gain for each spectrum,
- Triple coincidence from beam trigger finger conciliators (2 with PMT's, 1 with SiPM)
- Quadruple coincidence (3 PMT's, 1 SiPM and single SiPM
 - efficiency scan,
 - maximum efficiency reachable with single SiPM





- Both side-mounting and corner-mounting, counters have similar yields,
- Blind spots exist in both configurations,
- Side-mounting is easier,
- Trigger scan shows, that even one SiPM is enough with proper threshold

Generated/detected with FTOF wall





Generated/detected with FTOF wall



$\bar{\Lambda}$






p




\bar{p}



Decay length and m_X for Lambda-bar




Binary reactions



$h = \text{hyperons : } \Lambda, \Sigma, \dots \Omega_c$

$h = \text{mesons : } \dots D \dots$



Selection of inclusive Λ and anti Λ

$$\bar{p} + p \rightarrow \bar{\Lambda} + X$$

$$\bar{p} + p \rightarrow \Lambda + X$$

$$\bar{\Lambda} \rightarrow \bar{p} + \pi^+$$

$$\Lambda \rightarrow p + \pi^-$$

Selection criteria

- pair of hadrons detected with the FTOF wall
- hadrons in a pair are of opposite charge: $H^+ H^-$
- invariant mass calculated under assumption

$$m(H^-) = m_p \quad m(H^+) = m_\pi \quad \text{for } \bar{\Lambda} \quad m(H^-) = m_\pi \quad m(H^+) = m_p \quad \text{for } \Lambda$$

- time-of-flight from decay vertex to FTOF calculated



$$t = t_c \sqrt{\frac{m^2}{p^2} + 1} \quad t_c = \frac{L}{c} \quad |t(H^+) - t(H^-)| < 100 \text{ ps}$$

- Kinematic criterion



$$p(H^-) > p(H^+) \quad \text{for } \bar{\Lambda} \quad p(H^-) < p(H^+) \quad \text{for } \Lambda$$





Λ and anti Λ invariant masses, hadrons of opposite charge




Λ and anti Λ invariant masses, hadrons of opposite charge, time-of-flight criterion




Λ and anti Λ invariant masses, hadrons of opposite charge, time-of-flight criterion, kinematic criterion






*Pairs of hadrons with
opposite charge and
calculated $\Delta t_{start} < 100$ ps*



*Pairs of hadrons with
opposite charge and
calculated $\Delta t_{start} < 100$ ps
and $z_2 > 0.066$ cm*



FTOF wall and barrel TOF multiplicities

0.14×10^6 $\bar{p}p$ interactions generated

